
Identity Services Reference Collection

Networking, Internet, & Web: Services & Discovery



2007-05-14



Apple Inc.
© 2007 Apple Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

.Mac is a registered service mark of Apple Inc.

Apple, the Apple logo, Mac, and Mac OS are trademarks of Apple Inc., registered in the United States and other countries.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR

CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

Introduction **Introduction** 5

Part I **Classes** 7

Chapter 1 **CBGroupIdentity Class Reference** 9

Overview 9
Tasks 9
Class Methods 10
Instance Methods 10

Chapter 2 **CBIdentity Class Reference** 13

Overview 13
Tasks 13
Class Methods 14
Instance Methods 16

Chapter 3 **CBIdentityAuthority Class Reference** 21

Overview 21
Tasks 21
Class Methods 22
Instance Methods 23

Chapter 4 **CBIdentityPicker Class Reference** 25

Overview 25
Tasks 25
Instance Methods 26

Chapter 5 **CBUserIdentity Class Reference** 29

Overview 29
Tasks 29
Class Methods 30
Instance Methods 30

Document Revision History 33

Index 35

Introduction

This collection of documents provides the API reference for Identity Services. Identity Services is a technology that allows you to create, maintain and remove users and groups from a system. There are two parts to the Identity Services APIs: the Core Services Identity API and the Collaboration framework.

Classes

CBGroupIdentity Class Reference

Inherits from	CBIdentity : NSObject
Conforms to	NSCoding (CBIdentity) NSCopying (CBIdentity) NSObject (NSObject)
Framework	/System/Library/Frameworks/Collaboration.framework
Availability	Available in Mac OS X v10.5 and later.
Companion guide	Identity Services Programming Guide
Declared in	CBIdentity.h CBIdentityAuthority.h CBIdentityPicker.h

Overview

An object of the `CBGroupIdentity` class represents a group identity and is used for viewing the attributes of group identities from an identity authority. The principal attributes of a `CBGroupIdentity` object are a POSIX group identifier (GID) and a list of members.

Tasks

Finding Group Identities

+ [groupIdentityWithPosixGID:authority:](#) (page 10)

Returns the group identity with the given POSIX GID in the specified identity authority.

Group Identity Attributes

- [posixGID](#) (page 11)

Returns the POSIX GID of the identity.

- [members](#) (page 10)

Returns the members of the group.

Class Methods

groupIdentityWithPosixGID:authority:

Returns the group identity with the given POSIX GID in the specified identity authority.

```
+ (CBGroupIdentity *)groupIdentityWithPosixGID:(gid_t)gid
  authority:(CBIdentityAuthority *)authority
```

Parameters

gid

The GID of the group identity you are searching for.

authority

An identity authority in which to search for the group identity.

Return Value

The group identity object with the given GID in the specified identity authority, or `nil` if no identity exists with the specified GID.

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CBIdentity.h`

Instance Methods

members

Returns the members of the group.

```
- (NSArray *)members
```

Return Value

An array of `CBIdentity` objects each representing a member of the group identity.

Discussion

This method only returns direct members of a group, it does not return members of members. Both user and group identities can be members of a group, but a group cannot be a member of itself. You also cannot have “circular” membership, i.e. a group be a member of another group that is a member of the first group.

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CBIdentity.h`

posixGID

Returns the POSIX GID of the identity.

- (gid_t)posixGID

Return Value

The POSIX GID of the group identity.

Discussion

The POSIX GID is an integer that can identify a group within an identity authority. GIDs are not guaranteed to be unique within an identity authority.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentity.h

CBIdentity Class Reference

Inherits from	NSObject
Conforms to	NSCoding NSCopying NSObject (NSObject)
Framework	/System/Library/Frameworks/Collaboration.framework
Availability	Available in Mac OS X v10.5 and later.
Declared in	Collaboration/CBIdentity.h
Companion guide	Identity Services Programming Guide

Overview

A `CBIdentity` object is used for accessing the attributes of an identity stored in an identity authority. You can use an identity object for finding identities, and storing them in an access control list (ACL). If you need to edit these attributes, take advantage of the `CSIdentity` class in Core Services.

You can obtain a `CBIdentity` object from one of the following class factory methods:

`identityWithName:authority:`, `identityWithUUIDString:authority:`,
`identityWithPersistentReference:`, or `identityWithCSIdentity:`.

A `CBIdentity` object has methods to support for interoperability with the Core Services Identity API. Send `CSIdentity` to your `CBIdentity` object to return an opaque object for use in the Core Services Identity API. Similarly, call `identityWithCSIdentity:` to use an Core Services Identity opaque object in the Collaboration framework.

There are two subclasses of `CBIdentity`: `CBGroupIdentity` and `CBUserIdentity`. If you are working specifically with a group identity, use `CBGroupIdentity`. Similarly, if you are working with a user identity, use `CBUserIdentity`.

Tasks

Finding Identities

+ [identityWithCSIdentity:](#) (page 14)

Returns an identity object created from the specified Core Services Identity opaque object.

- + `identityWithName:authority:` (page 15)
Returns the identity object with the given name from the specified identity authority.
- + `identityWithPersistentReference:` (page 15)
Returns the identity object matching the persistent reference data.
- + `identityWithUUIDString:authority:` (page 16)
Returns the identity object with the given UUID from the specified identity authority.

Getting Identity Attributes

- `aliases` (page 16)
Returns an array of aliases (alternate names) for the identity.
- `authority` (page 17)
Returns the identity authority where the identity is stored.
- `emailAddress` (page 17)
Returns the email address of an identity.
- `fullName` (page 17)
Returns the full name of the identity.
- `image` (page 18)
Returns the image associated with an identity.
- `isHidden` (page 18)
Returns a Boolean value indicating the state of the identity's hidden property.
- `isMemberOfGroup:` (page 18)
Returns a Boolean value indicating whether the identity is a member of the specified group.
- `posixName` (page 19)
Returns the POSIX name of the identity.
- `UUIDString` (page 20)
Returns the UUID of the identity as a string.

Storing Identities

- `CSIdentity` (page 17)
Returns an opaque object for use with the Core Services Identity API.
- `persistentReference` (page 19)
Returns a persistent reference to store a reference to an identity.

Class Methods

identityWithCSIdentity:

Returns an identity object created from the specified Core Services Identity opaque object.

```
+ (CBIdentity *)identityWithCSIdentity:(CSIdentityRef)csIdentity
```

Parameters*csIdentity*

The Core Services Identity opaque object.

Return Value

The identity object for use with the Collaboration framework.

Discussion

This method is used for interoperability with the Core Services Identity API.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentity.h

identityWithName:authority:

Returns the identity object with the given name from the specified identity authority.

```
+ (CBIdentity *)identityWithName:(NSString *)name authority:(CBIdentityAuthority *)authority
```

Parameters*name*

The name of the identity.

authority

The identity authority to search.

Return ValueThe identity object, or `nil` if no identity is found with the specified name.**Discussion**

The name is compared against all valid identity names, including full names, short names, email addresses, and aliases.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentity.h

identityWithPersistentReference:

Returns the identity object matching the persistent reference data.

```
+ (CBIdentity *)identityWithPersistentReference:(NSData *)data
```

Parameters*data*

The persistent data object that refers to an identity.

Return ValueThe identity object matching the persistent data object, or `nil` if the identity is not found.

Discussion

A persistent reference is an opaque data object suitable for persistent storage.

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CBIdentity.h`

identityWithUUIDString:authority:

Returns the identity object with the given UUID from the specified identity authority.

```
+ (CBIdentity *)identityWithUUIDString:(NSString *)uuid
  authority:(CBIdentityAuthority *)authority
```

Parameters

uuid

The UUID of the identity you are searching for.

authority

The identity authority to search.

Return Value

The identity object, or `nil` if no identity is found with the matching criteria.

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CBIdentity.h`

Instance Methods

aliases

Returns an array of aliases (alternate names) for the identity.

```
- (NSArray *)aliases
```

Return Value

An array of `NSString` objects containing the alternate names for the identity.

Discussion

An identity can have zero or more aliases. Like the full and short names, two identities cannot share an alias.

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CBIdentity.h`

authority

Returns the identity authority where the identity is stored.

```
- (CBIdentityAuthority *)authority
```

Return Value

The identity authority where the identity is stored.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentity.h

CSIdentity

Returns an opaque object for use with the Core Services Identity API.

```
- (CSIdentityRef)CSIdentity
```

Return Value

The opaque object for use with the Core Services Identity API.

Discussion

This method, along with `identityWithCSIdentity:`, is used for interoperability with the Core Services Identity API.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentity.h

emailAddress

Returns the email address of an identity.

```
- (NSString *)emailAddress
```

Return Value

The email address of an identity or `nil` if none exists.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentity.h

fullName

Returns the full name of the identity.

- (NSString *)fullName

Return Value

The full name for the identity.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentity.h

image

Returns the image associated with an identity.

- (NSImage *)image

Return Value

The image associated with an identity, or `nil` if none exists.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentity.h

isHidden

Returns a Boolean value indicating the state of the identity's hidden property.

- (BOOL)isHidden

Return Value

YES if the identity is hidden; NO if it is not.

Discussion

A hidden identity does not show up in the Identity Picker. A hidden identity refers to system identities such as `root`, `www`, and `wheel`.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentity.h

isMemberOfGroup:

Returns a Boolean value indicating whether the identity is a member of the specified group.

- (BOOL)isMemberOfGroup:(CBGroupIdentity *)group

Parameters*group*

The group to check for membership.

Return Value

YES if the identity is a member of the group; NO if it is not.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentity.h

persistentReference

Returns a persistent reference to store a reference to an identity.

- (NSData *)persistentReference

Return Value

A data object that uniquely references an identity.

Discussion

A persistent reference data object is an object generated from an identity. Persistent data objects can be written to and read from a file, making them extremely useful for storing identities in an ACL.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentity.h

posixName

Returns the POSIX name of the identity.

- (NSString *)posixName

Return Value

The POSIX name of the identity.

Discussion

The POSIX name is also referred to as the “short name” for an identity. It can only contain the characters A-Z, a-z, 0-9, -, _, ., and @.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentity.h

UUIDString

Returns the UUID of the identity as a string.

```
- (NSString *)UUIDString
```

Return Value

The UUID string of the identity.

Discussion

The UUID string is generated so it is unique across all identity authorities. When storing ACLs, one method is to store the UUID of each identity. However, it is recommended that you use a persistent data object instead (see `persistentReference`).

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CBIdentity.h`

CBIdentityAuthority Class Reference

Inherits from	NSObject
Conforms to	NSObject (NSObject)
Framework	/System/Library/Frameworks/Collaboration.framework
Availability	Available in Mac OS X v10.5 and later.
Declared in	Collaboration/CBIdentityAuthority.h
Companion guide	Identity Services Programming Guide

Overview

An identity authority is a database that stores information about identities. The `CBIdentityAuthority` class defines one or more identity authorities. This database can be searched for identities in conjunction with the `CBIdentity` class factory methods.

Tasks

Interacting with the Core Services Identity API

- [CSIdentityAuthority](#) (page 23)
Returns an identity authority for use with the Core Services Identity API.
- + [identityAuthorityWithCSIdentityAuthority:](#) (page 22)
Returns an identity authority specified by a given Core Services Identity authority object.

Accessing Identity Authorities

- [localizedName](#) (page 24)
Returns the localized name of the identity authority.
- + [localIdentityAuthority](#) (page 23)
Returns the identity authority on the local system.
- + [managedIdentityAuthority](#) (page 23)
Returns the identity authority that contains all the identities in bound network directory servers.

+ [defaultIdentityAuthority](#) (page 22)

Returns an identity authority that contains the identities in both the local and the network-bound authorities.

Class Methods

defaultIdentityAuthority

Returns an identity authority that contains the identities in both the local and the network-bound authorities.

```
+ (CBIdentityAuthority *)defaultIdentityAuthority
```

Return Value

The local and network-bound identity authorities.

Discussion

The default identity authority is the logical union of the identities in the local and managed authorities.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentityAuthority.h

identityAuthorityWithCSIdentityAuthority:

Returns an identity authority specified by a given Core Services Identity authority object.

```
+ (CBIdentityAuthority *)identityAuthorityWithCSIdentityAuthority:(CSIdentityAuthorityRef)CSIdentityAuthority
```

Parameters

CSIdentityAuthority

The Core Services Identity opaque object.

Return Value

The identity authority object for use with the Collaboration framework.

Discussion

This method, along with `CSIdentityAuthority`, is used for interoperability with the Core Services Identity API.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentityAuthority.h

localIdentityAuthority

Returns the identity authority on the local system.

```
+ (CBIdentityAuthority *)localIdentityAuthority
```

Return Value

The identity authority on the local system.

Discussion

Any identities stored on the local system are contained within this identity authority.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentityAuthority.h

managedIdentityAuthority

Returns the identity authority that contains all the identities in bound network directory servers.

```
+ (CBIdentityAuthority *)managedIdentityAuthority
```

Return Value

The identity authorities in bound network directory servers.

Discussion

If you are bound to a network directory server (such as an LDAP server) that has an identity authority, use this method to search those authorities.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentityAuthority.h

Instance Methods

CSIdentityAuthority

Returns an identity authority for use with the Core Services Identity API.

```
- (CSIdentityAuthorityRef)CSIdentityAuthority
```

Return Value

The opaque authority object for use with the Core Services Identity API.

Discussion

This method, along with `identityAuthorityWithCSIdentityAuthority:`, is used for interoperability with the Core Services Identity API.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentityAuthority.h

localizedName

Returns the localized name of the identity authority.

- (NSString *)localizedName

Return Value

The computer's name if the authority is local, or Managed Network Directory if the authority is managed.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentityAuthority.h

CBIdentityPicker Class Reference

Inherits from	NSObject
Conforms to	NSObject (NSObject)
Framework	/System/Library/Frameworks/Collaboration.framework
Availability	Available in Mac OS X v10.5 and later.
Declared in	Collaboration/CBIdentityPicker.h
Companion guide	Identity Services Programming Guide

Overview

A `CBIdentityPicker` object allows a user to select identities—for example, user or group objects—that it wants one or more services or shared resources to have access to. An identity picker can be displayed either as an application-modal dialog or as a sheet attached to a document window. An identity picker returns the selected records to be added to access control lists using Collaboration. If a selected record is not a user or group identity, then an identity picker prompts the end user for additional information—such as a password—to promote that record to a sharing account.

Tasks

Running an Identity Picker

- [runModalForWindow:modalDelegate:didEndSelector:contextInfo:](#) (page 27)
Runs the receiver modally as a sheet attached to a specified window.
- [runModal](#) (page 27)
Runs the receiver as an application-modal dialog.

Retrieving Identities

- [identities](#) (page 26)
Returns an array of the identities selected using the identity picker.

Setting and Getting Properties

- `setTitle:` (page 28)
Sets the title of the identity picker.
- `title` (page 28)
Returns the title of the identity picker.
- `setAllowsMultipleSelection:` (page 28)
Allows a user to make select multiple identities.
- `allowsMultipleSelection` (page 26)
Returns a Boolean value indicating whether the user is allowed to select multiple identities.

Instance Methods

allowsMultipleSelection

Returns a Boolean value indicating whether the user is allowed to select multiple identities.

- (BOOL)allowsMultipleSelection

Return Value

YES if the user can select multiple records; otherwise, NO.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentityPicker.h

identities

Returns an array of the identities selected using the identity picker.

- (NSArray *)identities

Return Value

An array of the selected identities.

Discussion

The array contains `CBIdentity` objects.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentityPicker.h

runModal

Runs the receiver as an application-modal dialog.

```
- (NSInteger)runModal
```

Return Value

NSOKButton if the user selected OK; otherwise, NSCancelButton.

Discussion

The receiver may create identities for selected records if necessary.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentityPicker.h

runModalForWindow:modalDelegate:didEndSelector:contextInfo:

Runs the receiver modally as a sheet attached to a specified window.

```
- (void)runModalForWindow:(NSWindow *)window modalDelegate:(id)delegate
    didEndSelector:(SEL)didEndSelector contextInfo:(void *)contextInfo
```

Parameters

window

The parent window for the sheet.

delegate

The delegate for the modal session.

didEndSelector

A message sent to the delegate after the user responds but before the sheet is dismissed.

contextInfo

Contextual data passed to the delegate in the `didEndSelector` message.

Discussion

The `didEndSelector` parameter is a selector that takes three arguments. The corresponding method should have a declaration modeled on the following example:

```
- (void)identityPickerDidEnd:(CBIdentityPicker *)identityPicker
    identities:(NSArray *)identities contextInfo:(void *)contextInfo;
```

where the `identityPicker` argument is the identity picker object, the `identities` argument is an array containing `CBIdentity` objects, and `contextInfo` is the same `contextInfo` argument that was passed in the original message.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentityPicker.h

setAllowsMultipleSelection:

Allows a user to make select multiple identities.

```
- (void)setAllowsMultipleSelection:(BOOL)flag
```

Parameters

flag

YES if you can select multiple records; otherwise, NO.

Discussion

By default, you cannot select multiple records.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentityPicker.h

setTitle:

Sets the title of the identity picker.

```
- (void)setTitle:(NSString *)title
```

Parameters

title

The title of the identity picker.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentityPicker.h

title

Returns the title of the identity picker.

```
- (NSString *)title
```

Return Value

The title of the identity picker.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentityPicker.h

CBUserIdentity Class Reference

Inherits from	CBIdentity : NSObject
Conforms to	NSCoding NSCopying NSCoding (CBIdentity) NSCopying (CBIdentity) NSObject (NSObject)
Framework	/System/Library/Frameworks/Collaboration.framework
Availability	Available in Mac OS X v10.5 and later.
Declared in	Collaboration/CBIdentity.h
Companion guide	Identity Services Programming Guide

Overview

An object of the `CBUserIdentity` class represents a user identity and is used for accessing the attributes of a user identity from an identity authority. The principal attributes of `CBUserIdentity` are a POSIX user identifier (UID), password, and certificate.

Tasks

Password Authentication

- [authenticateWithPassword:](#) (page 30)
Returns a Boolean value indicating whether the given password is correct for the identity.
- [certificate](#) (page 31)
Returns the public authentication certificate associated with a user identity.
- [isEnabled](#) (page 31)
Returns a Boolean value indicating whether the identity is allowed to authenticate.

Using UIDs

- [posixUID](#) (page 31)
Returns the POSIX UID of the identity.

+ [userIdentityWithPosixUID:authority:](#) (page 30)

Returns the user identity with the given POSIX UID in the specified identity authority.

Class Methods

userIdentityWithPosixUID:authority:

Returns the user identity with the given POSIX UID in the specified identity authority.

```
+ (CUserIdentity *)userIdentityWithPosixUID:(uid_t)uid  
  authority:(CIdentityAuthority *)authority
```

Parameters

uid

The UID of the identity you are searching for.

authority

The identity authority to search.

Return Value

The user identity with the given UID in the specified identity authority, or `nil` if no identity exists with the specified UID.

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CIdentity.h`

Instance Methods

authenticateWithPassword:

Returns a Boolean value indicating whether the given password is correct for the identity.

```
- (BOOL)authenticateWithPassword:(NSString *)password
```

Parameters

password

The password to test for the identity.

Return Value

TRUE if the password is correct; otherwise, FALSE.

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CIdentity.h`

certificate

Returns the public authentication certificate associated with a user identity.

- (SecCertificateRef)certificate

Return Value

The public authentication certificate, or `nil` if none exists.

Discussion

The Collaboration framework supports certificate-based authentication in addition to passwords. If a certificate is stored for a user identity, it will be the default method of authentication.

When a .Mac account is associated with a user identity, the authentication certificate is automatically downloaded from the .Mac servers.

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CBIdentity.h`

isEnabled

Returns a Boolean value indicating whether the identity is allowed to authenticate.

- (BOOL)isEnabled

Return Value

TRUE if the identity can authenticate; otherwise, FALSE.

Discussion

If the identity does not have authentication credentials (a password or certificate), it is not able to log in. However, an identity with authentication credentials does not ensure that it is enabled. Any identity can be disabled.

Availability

Available in Mac OS X v10.5 and later.

Declared In

`CBIdentity.h`

posixUID

Returns the POSIX UID of the identity.

- (uid_t)posixUID

Return Value

The POSIX UID of the identity.

Discussion

The POSIX UID is an integer that can identify a user within an identity authority. UIDs are not guaranteed to be unique within an identity authority.

Availability

Available in Mac OS X v10.5 and later.

Declared In

CBIdentity.h

Document Revision History

This table describes the changes to *Identity Services Reference Collection*.

Date	Notes
2007-05-14	New document that describes the APIs for using identities and the Identity Picker.

REVISION HISTORY

Document Revision History

Index

A

aliases **instance method** [16](#)
allowsMultipleSelection **instance method** [26](#)
authenticateWithPassword: **instance method** [30](#)
authority **instance method** [17](#)

C

certificate **instance method** [31](#)
CSIdentity **instance method** [17](#)
CSIdentityAuthority **instance method** [23](#)

D

defaultIdentityAuthority **class method** [22](#)

E

emailAddress **instance method** [17](#)

F

fullName **instance method** [17](#)

G

groupIdentityWithPosixGID:authority: **class method** [10](#)

I

identities **instance method** [26](#)
identityAuthorityWithCSIdentityAuthority:
 class method [22](#)
identityWithCSIdentity: **class method** [14](#)
identityWithName:authority: **class method** [15](#)
identityWithPersistentReference: **class method**
 [15](#)
identityWithUUIDString:authority: **class method**
 [16](#)
image **instance method** [18](#)
isEnabled **instance method** [31](#)
isHidden **instance method** [18](#)
isMemberOfGroup: **instance method** [18](#)

L

localIdentityAuthority **class method** [23](#)
localizedName **instance method** [24](#)

M

managedIdentityAuthority **class method** [23](#)
members **instance method** [10](#)

P

persistentReference **instance method** [19](#)
posixGID **instance method** [11](#)
posixName **instance method** [19](#)
posixUID **instance method** [31](#)

R

runModal **instance method** [27](#)

runModalForWindow:modalDelegate:didEndSelector:
contextInfo: **instance method** [27](#)

S

setAllowsMultipleSelection: **instance method** [28](#)
setTitle: **instance method** [28](#)

T

title **instance method** [28](#)

U

userIdentityWithPosixUID:authority: **class**
method [30](#)
UUIDString **instance method** [20](#)